358 Series M mass flow meters

Multi-parameter laminar mass flow meters from 50 sL/min to 5000 sL/min full scale

The M meter measures gas mass flow and also reports volumetric flow, pressure and temperature on its display. It stores 98 gases and 20 user mixes, so one instrument serves many processes. RS-232 and Modbus RTU are standard; analogue outputs and fieldbus interfaces are options.



5000 sL/min	0.01–100 %	< 1 ms	98	11.0 bar a
Largest full scale; the smallest is 50 sL/min	Flow measurement range of full scale	Sensor response time	Stored gases, plus 20 user-defined mixes	Maximum operating pressure (160 psia)

Performance

Reference conditions	Standard 21.11 °C, normal 0 °C, at 1013.25 mbar; configurable
Accuracy [1]	±(0.8 % rd + 0.2 % FS)
High-accuracy option [1]	50–500 sL/min: ±(0.4 % rd + 0.2 % FS)
Repeatability (2σ)	±(0.2 % rd + 0.02 % FS)
Flow measurement range	0.01–100 % FS
Turndown ratio	10 000:1
Indication response	Typically < 10 ms, flow rate dependent
Sensor response	< 1 ms
Warm-up time	Typically < 1 s
Temperature sensitivity	Zero and span ±0.02 % FS/°C from 25 °C
Pressure sensitivity	Zero and span ±(0.08 % rd + 0.02 % FS)/atm from calibration conditions
Pressure accuracy [1]	Above 1 atm: ±0.5 % rd Below 1 atm: ±4.8 mbar (±0.07 psia)
Temperature accuracy	±0.75 °C
Totaliser	±0.1 % rd additional uncertainty

Operating conditions

Operating pressure	0.79–11.0 bar a (11.5–160 psia)
Damage limits	Line: above 13.8 bar a (200 psia) Rapid change: above 5.17 bar (75 psid)
Temperature	−10 to 60 °C, ambient and gas
Humidity	0–95 % non-condensing

Mechanical

Wetted materials	Stainless steel 302, 303, 304, 316L; FKM, alumina ceramic, glass, gold, silicon, polyamide Heat-cured epoxy and silicone rubber
Ingress protection	IP40
Mounting holes	4× 8-32 UNC, 8.38 mm deep

Electrical and communication

Analogue outputs	4–20 mA, 0–5 V DC, 1–5 V DC or 0–10 V DC; adds ±0.1 % FS uncertainty
Digital I/O	Standard: RS-232 and Modbus RTU Options: RS-485, Modbus TCP/IP, DeviceNet, EtherCAT, EtherNet/IP, PROFIBUS, PROFINET, IO-Link
Connector	6-pin locking, 8-pin mini-DIN, 8-pin M12, DB-9 or DB-15; custom pinouts: ask Analyt-MTC
Supply [2]	0–5 V DC output: 9–24 V DC, 40 mA 0–10 V DC output: 12–28 V DC, 40 mA 4–20 mA output: 12–28 V DC, 80 mA
Update rates [2]	Digital: 40 Hz at 19 200 baud Analogue: 1 kHz; display: 10 Hz


Display and gases

Display	Monochrome LCD or colour TFT, touchpad; shows mass and volumetric flow, pressure, temperature
Gas library	98 gases, properties matched to NIST REFPROP 10 across the operating range
Gas mixes	20 user mixes of up to 5 gases, 0.01 % resolution

Ranges, pressure drop, connections (21.11 °C, 1013.25 mbar)

Full scale	Δp, mbar	psid	Process connection
50 sL/min	138	2.0	1/4" NPT female
100 sL/min	172	2.5	1/4" NPT female
250 sL/min	145	2.1	1/2" NPT female
500 sL/min	276	4.0	3/4" NPT female
1000 sL/min	414	6.0	3/4" NPT female
2000 sL/min	345	5.0	3/4" NPT female
3000 sL/min	490	7.1	1 1/4" NPT female
5000 sL/min	234	3.4	2" NPT female

Δp at full scale, venting air to atmosphere; for a lower Δp, ask Analyt-MTC. For full-scale ranges above 5000 sL/min, ask Analyt-MTC.



1 DC power input
2 Input and output port
3 Controls
4 Backlight switch
5 Process connection

Top view; two side views and the front view; bottom view with mounting holes. One drawing serves every meter from 50 to 5000 sL/min; the table gives the dimensions.

Dimensions, mm and kg (21.11 °C, 1013.25 mbar)

Full scale	W	D	H	A	B	C	E	F	G	kg
50 sL/min	101.6	40.6	110.9	12.7	20.3	4.4	36.2	19.1	82.6	≈ 1.1
100 sL/min	101.6	40.6	110.9	12.7	20.3	4.4	36.2	19.1	82.6	≈ 1.1
250 sL/min	101.6	40.6	126.2	20.3	20.3	4.4	36.2	19.1	82.6	≈ 1.1
500–1000 sL/min	101.6	40.6	126.2	20.3	20.3	4.4	36.2	19.1	82.6	≈ 1.6
2000 sL/min	132.1	73.7	134.3	28.4	36.8	5.1	68.6	34.3	97.8	≈ 2.0
3000 sL/min	132.1	73.7	134.3	24.4	36.8	5.1	68.6	34.3	97.8	≈ 2.0
5000 sL/min	132.1	97.5	159.2	36.8	48.8	7.5	90.0	34.3	97.8	≈ 6.4

Standard versions, air (21.11 °C, 1013.25 mbar)

Full scale	Order code
50 sL/min	35815
100 sL/min	35816
250 sL/min	35817
500 sL/min	35818
1000 sL/min	35819

Order from Analyt-MTC with the order codes. Calibrated for air; another gas or a gas mix is selected on the meter. For any other version, contact Analyt-MTC.

Options and accessories

High-accuracy calibration, 50–500 sL/min (see Accuracy)	
Weatherproof housing	
Compression, face-seal, push-to-connect, BSPP or SAE connections	
Swagelok®-compatible tube, VCO® or VCR® connections	
Universal benchtop baseplate	35780
RS-232 cable, 8-pin mini-DIN to DB-9, 1.8 m	35754
USB to RS-232 adapter	35782
Inline filter, 1/4" NPT, 40 µm	ILF-1/4-40
Inline filter, 1/2" NPT, 40 µm	ILF-1/2-40
Inline filter, 3/4" NPT, 40 µm	ILF-3/4-40
Rugged transport case	1200-000-110E

Notes

1. rd = of reading, FS = of full scale. Accuracy holds after tare at equilibrium and includes repeatability and linearity. sL/min and smL/min at 21.11 °C, 1013.25 mbar.
2. Fieldbus versions differ in supply and data rates; ask Analyt-MTC for their documentation.

ANALYT-MTC Messtechnik GmbH
Sales, service and calibration

www.analyt-mtc.com

German Headquarters
Klosterrunsstraße 18, 79379 Müllheim
+49 7631 5545
info@analyt-mtc.de

French Subsidiary
175 Avenue d'Alsace, 68000 Colmar
+33 3 89 41 47 78
info@analyt-mtc.fr

© 2026 ANALYT-MTC Messtechnik GmbH. All rights reserved. Subject to technical changes without notice.